

## TECHNICAL DATA SHEET

### VARYBOND VB 70 GASKET REMOVER

**Art. No. 170161VAR**

VARYBOND VB 70 GASKET REMOVER can be applied everywhere where sticking adhesive, sealant, packaging or lacquer residues have to be removed in a rapid and effortless way. With GASKET REMOVER, the use of mechanical remedies are unnecessary. GASKET REMOVER can be applied on metal, wood, glass, ceramics, polyethylene and polypropylene. It is not recommendable to apply it on sensitive plastics, such as PVC, synthetics or linoleum. Test plastic compatibility before use.

GASKET REMOVER is a strong, thixotropic mixture of active substances. Its particularly strong solving effect makes the application extremely easy (even on vertical surfaces).

The product is mainly used in industry, garages and other trades where sticking residues have to be removed in a rapid and gentle way.

- removes cylinder, exhaust manifold packings and hardened sealants, such as engine sealants
- dissolves even the most stubborn adhesive residues, such as anaerobic products and adhesive made of cyanacrylic resin.
- removes, without effort, paints, lacquers, oils, resins as well as oil carbon, tar, grease and lubricant residues.

#### **Use:**

Shake the aerosol vigorously before use. Spray the surface needing treatment from a distance of approx. 25 cm. After applying the product, let it work into the surface for about 5 to 10 minutes. The partially dissolved residues are then carefully removed with the help of a scraper.

#### **Content of aerosol can:**

400 ml

Our information sheets and other publications are intended to provide advice based on the best knowledge at our disposal. However, contents are not legally binding with regards to processing and application as these do not fall within our field influence. The right is reserved to make modifications in the interests of improvement or further development of the product.